

**SNAPPY**

LED POWER SUPPLY DATASHEET



SE30-24VL

·DESCRIPTION

High Cost Performance,SELV. Open circuit, short circuit,overload protection.Compliance to ERP directive,lifetime 30,000hrs.



·Input

Items	Conditions	Request	Note	
Input voltage	Ta	180-264Vac	--	
Input frequency		50/60Hz	--	
Input current	25°C, rated input voltage, output with max. rated power	<0.25A	--	
Input power		<37W	--	
Efficiency		≥ 85 %	--	
Standby		25°C, rated input voltage, output without load	<0.5W	average
Inrush current		25°C, rated input voltage	<60A	peak
PF	25°C, rated input voltage, output max. rated power	≥ 0.9	--	

·Output

Items	Conditions	Request	Note
Startup time	25°C, rated input voltage, output with max. rated power	<0.5S	--
Output voltage and precision	Ta, rated input voltage, output with rated power	24V±5%	--
Output current range	Ta, rated input voltage	0-1.25A	30W
Output voltage wave	25°C, rated input voltage, output with max. rated power	<240mV	Vp-p
Output overload	25°C, rated input voltage, output with twice LED load	Yes	--
Output current and precision	Ta, rated input voltage, output with rated power	--	--
Rated output voltage range	Ta, rated input voltage	--	--
Output current wave	25°C, rated input voltage, output with max. rated power	--	Ip-p
Dimming mode	CV Dimming	--	--
Dimming range	0-100%	--	--

·Temperate and others

Items	Conditions	Request	Note
Operation temp.	--	-20~45°C	--
Relative humidity	--	45%-85%	--
Max. case temp.	--	80°C	--
Lifetime	Max.Ta,rated input voltage,output with max.rated power	30,000hr	--
Working noise	25°C, rated input voltage, output with rated power, mute box background noise<35dB, pickup 10cm distance from products	Yes	--

·Mechanical, mounting

Items	Conditions
Case material and size	Plastic case L149*W40.4*H26.7mm
Mounting ways	Independent
Insulation type	Class II
IP grade	IP20
Input cables dimension	H03VVH2-F 2*0.75mm2
Output cables dimension	H03VVH2-F 2*0.75mm2
Output cables length	--


·Protection

Item	Conditions	Request	Note
Open circuit	Ta, rated input voltage, no load	--	--
Over load	Ta, 0.94-1.06 times of input voltage, 1.4 times of rated power	Yes	--
Short circuit	Ta, 0.94-1.06 times of input voltage	Yes	--
Over temperature	Ta, 0.94-1.06 times of input voltage, temperature detected point more than 115 degree	--	--
Over voltage	Ta, 0.94-1.06 times of input voltage,output voltage is 1.5 times of rated one	--	--
Auto recovery	Over load,short circuit revocation	Yes	--
Latch off	Over temperature re-start after cut off	--	--

·Standard

Items	Conditions
Safety	IEC61347-1, IEC61347-2-13
Harmonic	EN61000-3-2 Class C
EMI	EN55015
EMS	EN61000-4-2, 3, 4, 5, 6 EN61547

● Dimensions(mm)



● Wiring Diagram

