

Local, Caution Spotlight Fittings BAJ52-20 Series Explosion-proof Emergency Light Fittings



- ◆ Explosion protection to
 - CENELEC
 - IEC
 - NEC
- ◆ Can be used in
 - Zone 1 and Zone 2
 - Class I, Zone 1 and Zone 2
 - Class I, Division 1, Groups C, D
- ◆ Enclosure in Copper-free Aluminium Alloy, powder coated surface, yellow (RAL1021).
- ◆ Lighting angle can be adjusted.
- ◆ Low-power halogen tungsten lamps, with reflector to increase lighting intensity.
- ◆ Emergency device with Ni-MH batteries, charging automatically; when power supply is cut off, the emergency device starts to work; with overcharge and overdischarge protection.
- ◆ Toughened glass cover resistant to temperature changes.



Zones 1&2

Local, Caution Spotlight Fittings

BAJ52-20 Series Explosion-proof Emergency Light Fittings

Technical data

Explosion-proof emergency light fittings BAJ52-20

Explosion protection

Global (IECEX)	IECEX CQM 08. 0001
Gas and dust	Ex d IIB T4 Gb
Europe (ATEX)	LCIE 07 ATEX 6086
Gas and dust	Ⓔ II 2 G Ex d IIB T4

Certificates

IECEX; ATEX

Conformity to standards

EN 60079-0, EN 60079-1
IEC 60079-0, IEC 60079-1

Material

Enclosure Copper-free Aluminium Alloy, powder coated surface, yellow (RAL1021)

Exposed fastener Stainless steel

Rated voltage

220~240V AC 50/60Hz

Lamp

Available lamp Halogen tungsten lamp (LED on request)

Lamp power (W) 2 x 10W (LED lamp power: 2 x 1W)

Emergency time 90min

Rated luminous flux Halogen tungsten lamp: 2 x 100lm (LED lamp: 2 x 90lm)

Battery

Description Ni-MH battery

Rated capacity 6Ah

Rated voltage 6V

Charging current 300mA

Discharging current 1000mA

Charging time 24h

Degree of protection

IP65

Ambient temperature

-20°C~+55°C

Terminal

3 x 1.5~2.5mm² (L+N+PE)

Cable entries

2 x M25 x 1.5 plugs

Cable gland (optional)

DQM-II (Ex d) or DQM-III (Ex d) is recommended. Please see P7/20~29.

Weight

5.05kg



Dimension drawings (all dimensions in mm) - subject to alteration

