

Dehumidifier parameters

- 1.Model: DJ-201B
- 2.Dehumidifying capacity: 20L/day (30℃, 80%RH)
- 3.Power supply: 220V-50Hz
- 4.Electric current: 3A
- 5.Input power: 400W
- 6.Operation temperature: 5-38℃
- 7.Drainage manner: drainage with tank or external hose
- 8.Unit dimension: 400*350*650 (mm)
- 9.Gross weight: 17Kg
- 10.Net weight: 15Kg
- 11.Application area: 10-30m² (Height2.6m)
12. Automatic defrost:automatic humidity control and defrost
13. Move: can move freely with swivel castors
- 14.Air direction: adjustable
- 15.Packaging: Carton



Dehumidifier parameters

1. Model: DJ-261B

Hangzhou dry air treatment equipment limited company

2. Dehumidifying capacity: 26L/day (30°C, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 3.4A
5. Input power: 450W
6. Operation temperature: 5-38°C
7. .Drainage manner: drainage with tank or external hose
8. Unit dimension: 400*350*650 (mm)
9. Gross weight: 18Kg
10. Net weight: 16Kg
11. Application area: 20-40 m² (Height 2.6m)
12. Automatic defrost:automatic humidity control and defrost
13. Move: can move freely with swivel castors
- 14.Air direction: adjustable
15. Packaging: Carton



Dehumidifier parameters

1. Model: DJ-201E
2. Humidity treatment: 20L/day (30°C, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 2.5A
5. Input power: 500W

Hangzhou dry air treatment equipment limited company

6. Surround T: 5-38℃
7. Drainage manner: Tank-type connections, large capacity water tank, It will continuous drainage after the tank is full
8. Size: 370*345*665 (mm)
9. Gross weight: 22Kg
10. Net weight: 18Kg
11. Adapted scope: 10-25 m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packaging: Carton



Dehumidifier parameters

1. Model: DJ-261E
2. Humidity treatment: 26L/day (30℃, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 3.0A
5. Input power: 550W
6. Surround T: 5-38℃
7. Drainage manner: Tank-type connections, large capacity water

Hangzhou dry air treatment equipment limited company

tank,It will continuous drainage after the tank is full

8. Size: 370*345*665 (mm)
9. Gross weight: 23Kg
10. Net weight: 20Kg
11. Adapted scope: 20-35 m² (Height 2.6m)
12. Automatic defrost:automatic humidity control and defrost
13. Move: can move freely with Wheels
- 14.Air direction: adjustable
15. Packaging: Carton



Dehumidifier parameters

1. Model: DJ-381E
2. Humidity treatment: 38L/day (30℃, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 3.0A
5. Input power: 650W
6. Surround T: 5-38℃
7. Drainage manner: Tank-type connections,large capacity water tank,stop when it is full
8. Size: 530*415*715 (mm)

Hangzhou dry air treatment equipment limited company

- 9. Gross weight: 30Kg
- 10. Net weight: 28Kg
- 11. Adapted scope: 30-40 m² (Height 2.6m)
- 12. Automatic defrost: automatic humidity control and defrost
- 13. Move: can move freely with Wheels
- 14. Air direction: adjustable
- 15. Packing: Carton



Dehumidifier parameters

- 1. Model: DJ-581E
- 2. Humidity treatment: 58L/day (30℃, 80%RH)
- 3. Power supply: 220V-50Hz
- 4. Electric current: 3.2A
- 5. Input power: 750W
- 6. Surround T: 5-38℃
- 7. Drainage manner: Tank-type connections, large capacity water tank, stop when it is full
- 8. Size: 530*415*715 (mm)
- 9. Gross weight: 32Kg
- 10. Net weight: 30Kg

Hangzhou dry air treatment equipment limited company

11. Adapted scope: 40-60 m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Carton



Dehumidifier parameters

1. Model: DJ-301B
2. Humidity treatment: 30L/day (30°C, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 2.5A
5. Input power: 670W
6. Surround T: 5-38°C
7. Drainage manner: Tank-type connections, large capacity water tank, stop when it is full
8. Size: 530X430X650 (mm)
9. Gross weight: 26Kg
10. Net weight: 24Kg
11. Adapted scope: 30-50 m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels

14. Air direction: adjustable

15. Packing: Carton



Dehumidifier parameters

1. Model: DJ-501B
2. Humidity treatment: 50L/day (30℃, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 3.0A
5. Input power: 720W
6. Surround T: 5-38℃
7. Drainage manner: Tank-type connections, large capacity water tank, stop when it is full
8. Size: 530X430X650 (mm)
9. Gross weight: 27Kg
10. Net weight: 25Kg
11. Adapted scope: 50-70m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels

14. Air direction: adjustable

15. Packing: Carton



Dehumidifier parameters

1. Model: DJ-901E

2. Humidity treatment: 90L/day (30°C, 80%RH)

3. Power supply: 220V-50Hz

4. Electric current: 7.5A

5. Input power: 1500W

6. Surround T: 5-38°C

7. Drainage manner: soft tube connection, continuous drainage

8. Size: 540*460*1025 (mm)

9. Gross weight: 53Kg

10. Net weight: 50Kg

11. Adapted scope: 90-120m² (Height 2.6m)

12. Automatic defrost: automatic humidity control and defrost

13. Move: can move freely with Wheels

14. Air direction: adjustable

15. Packing: Carton



Dehumidifier parameters

1. Model: DJ-1301E
2. Humidity treatment: 130L/day (30℃, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 9.0A
5. Input power: 1700W
6. Surround T: 5-38℃
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 540X460X1025 (mm)
9. Gross weight: 60Kg
10. Net weight: 53Kg
11. Adapted scope: 100-130m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Carton



Dehumidifier parameters

1. Model: DJ-1381E
2. Humidity treatment: 138L/day (30℃, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 10.0A
5. Input power: 2100W
6. Surround T: 5℃ -38℃
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 540*460*1125 (mm)
9. Gross weight: 57Kg
10. Net weight: 55Kg
11. Adapted scope: 120-150m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Carton



Dehumidifier parameters

1. Model: DJ-1501E
2. Humidity treatment: 150L/day (30℃, 80%RH)
3. Power supply: 220V-50Hz
4. Electric current: 11.0A
5. Input power: 2200W
6. Surround T: 5℃ -38℃
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 540*460*1125 (mm)
9. Gross weight: 57Kg
10. Net weight: 55Kg
11. Adapted scope: 130-170m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Carton



Dehumidifier parameters

1. Model: DJ-1681E

Hangzhou dry air treatment equipment limited company

2. Humidity treatment: 168L/day (27℃, 70%RH)
3. Power supply: 380V-50Hz
4. Electric current: 6.0A
5. Input power: 3000W
6. Surround T: 5℃ - 38℃
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 620X400X1600 (mm)
9. Gross weight: 150Kg
10. Net weight: 123Kg
11. Adapted scope: 160-220m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Wooden case



Dehumidifier parameters

1. Model: DJ-2181E
2. Humidity treatment: 200L/day (27℃, 70%RH)
3. Power supply: 380V-50Hz

Hangzhou dry air treatment equipment limited company

4. Electric current: 8.0A
5. Input power: 4200W
6. Surround T: 5℃ - 38℃
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 790X470X1620 (mm)
9. Gross weight: 160Kg
10. Net weight: 140Kg
11. Adapted scope: 220-300m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Wooden case



Dehumidifier parameters

1. Model: DJ-2481E
2. Humidity treatment: 248L/day (27℃, 70%RH)
3. Power supply: 380V-50Hz
4. Electric current: 12.0A
5. Input power: 5200W

Hangzhou dry air treatment equipment limited company

6. Surround T: 5℃ - 38℃
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 790X470X1720 (mm)
9. Gross weight: 170Kg
10. Net weight: 150Kg
11. Adapted scope: 300-400m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Wooden case



Dehumidifier parameters

1. Model: DJ-2881E
2. Humidity treatment: 12kg/h (27℃, 70%RH)
3. Power supply: 380V-50Hz
4. Electric current: 13.0A
5. Input power: 6000W
6. Surround T: 5℃ - 38℃
7. Drainage manner: soft tube connection, continuous drainage

Hangzhou dry air treatment equipment limited company

8. Size: 790X470X1720 (mm)
9. Gross weight: 220Kg
10. Net weight: 190Kg
11. Adapted scope: 350-450m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Wooden case



Dehumidifier parameters

1. Model: DJ-3881E
2. Humidity treatment: 388L/day (27°C, 70%RH)
3. Power supply: 380V-50Hz
4. Electric current: 13A
5. Input power: 8100W
6. Surround T: 5°C - 38°C
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 1200X450X1750 (mm)
9. Gross weight: 220Kg
10. Net weight: 200Kg

Hangzhou dry air treatment equipment limited company

11. Adapted scope: 400-500m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost
13. Move: can move freely with Wheels
14. Air direction: adjustable
15. Packing: Wooden case



Dehumidifier parameters

1. Model: DJ-4881E
2. Humidity treatment: 480L/day (27°C, 70%RH)
3. Power supply: 380V-50Hz
4. Electric current: 16A
5. Input power: 10500W
6. Surround T: 5°C - 38°C
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 1200X450X1750 (mm)
9. Gross weight: 240Kg
10. Net weight: 220Kg
11. Adapted scope: 500-600m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost

Hangzhou dry air treatment equipment limited company

13. Move: can move freely with Wheels

14. Air direction: adjustable

15. Packing: Wooden case



Dehumidifier parameters

1. Model: DJ-6181E

2. Humidity treatment: 600L/day (27°C, 70%RH)

3. Power supply: 380V-50Hz

4. Electric current: 16A

5. Input power: 11500W

6. Surround T: 5°C - 38°C

7. Drainage manner: soft tube connection, continuous drainage

8. Size: 1200X450X1750 (mm)

9. Gross weight: 320Kg

10. Net weight: 280Kg

11. Adapted scope: 600-700m² (Height 2.6m)

12. Automatic defrost: automatic humidity control and defrost

13. Move: can move freely with Wheels

14. Air direction: adjustable

15. Packing: Wooden case



Dehumidifier parameters

1. Model: DJ-7281E
2. Humidity treatment: 720L/day (27°C, 70%RH)
3. Power supply: 380V-50Hz
4. Electric current: 19.3A
5. Input power: 12.6KW
6. Surround T: 5°C - 38°C
7. Drainage manner: soft tube connection, continuous drainage
8. Size: 1400X650X1930 (mm)
9. Gross weight: 400Kg
10. Net weight: 340Kg
11. Adapted scope: 700-900m² (Height 2.6m)
12. Automatic defrost: automatic humidity control and defrost

13. Move: can move freely with Wheels

14. Air direction: adjustable

15. Packing: Wooden case



Dehumidifier parameters

1. Model: DJ-9681E

2. Humidity treatment: 960 升/天 (27℃, 70%RH)

3. Power supply: 380V-50Hz

4. Electric current: 25.8A

5. Input power: 16.9KW

6. Surround T: 5℃ -38℃

7. Drainage manner: soft tube connection, continuous drainage

8. Size: 1400X650X1930 (mm)

9. Gross weight: 500Kg

10. Net weight: 440Kg

11. Adapted scope: 900-1100m² (Height 2.6m)

12 . Automatic defrost: automatic humidity control and defrost

13. Move: can move freely with Wheels



Hangzhou dry air treatment equipment limited company

14.Air direction: adjustable

15.Packing: Wooden case